

Unmanaged Switch PROmesh U16

PROmesh U16



Art.-Nr.: 114110124

HIGHLIGHTS



16 RJ45 Ports



Industry Applications

- PROFINET



Country approvals

- CE | UKCA



Performance

- Memory: 1 Mbit
- Backplane capacity: 3,2 Gbit/s
- Throughput: 2,4 Mpp



Sustainability

- Lead-free
- Lowpower consumption

Unmanaged Switch PROmesh U16

Technical details

Network interfaces	
RJ45 Ports	
■ Interfaces	16
■ Transmission rates	10 Mbit/s 100 Mbit/s
■ Status LED	Link + Data communication
Supply voltage, current consumption	
Connections	
■ Power supply	4 x 0,2 – 2,5 mm ²
■ Functional earthing	Grounding screw
Operating parameters	
■ Supply voltage (nominal value)	24 VDC
■ Supply voltage (min.)	9 VDC
■ Supply voltage (max.)	60 VDC
Environmental conditions	
■ Operating temperature	-40°C ... +75°C
■ Storage temperature	-40°C ... +85°C
■ Humidity, rel.	<95% RHD, non-condensing
Design, Dimensions, Weights	
■ Design	Compact, passive cooling
■ Material (housing)	sheet metal bending housing, painted
■ Mounting	35 mm DIN-rail (0°, 90°)
■ Width	53 mm
■ Height	138 mm
■ Depth	110 mm
■ Mounting distance (Vertical)	20 mm
■ Mounting distance (horizontal)	20 mm
Further device interfaces	
■ Status LED	Yes
■ DIP-Switches	Yes
Functions	
Basic parameters	
■ Switching Technology	Store & Forward
■ MAC address table	2 K
■ Packet memory	1 Mbit
■ Backplane capacity	3,2 Gbit/s
■ Throughput	2,4 Mpps

Unmanaged Switch PROmesh U16

Technical details

Dip-Schalter	
<ul style="list-style-type: none"> Storm Suppression 	Set the switch to „ON“ to limit the effects of network storms.
<ul style="list-style-type: none"> Flow Control 	Set the switch to „ON“ so that the switch, as soon as it is heavily loaded, informs the connected units that they should stop transmitting for a short time.
Application-specific	
Protocols/Services	
<ul style="list-style-type: none"> PROFINET Conformity Class 	A
Standards, guidelines, approvals	
EMC	
<ul style="list-style-type: none"> Directive 	2014/30/EU
<ul style="list-style-type: none"> interference emission 	EN 55032
<ul style="list-style-type: none"> noise immunity 	EN 61000-6-2
Mechanical stability	
<ul style="list-style-type: none"> Vibration 	IEC 60068-2-6
<ul style="list-style-type: none"> Shock 	IEC 60068-2-27
<ul style="list-style-type: none"> Free Fall 	IEC 60068-2-32
Approval	
<ul style="list-style-type: none"> Europe 	CE/UKCA
Environment	
<ul style="list-style-type: none"> RoHS 	2011/65/EU
<ul style="list-style-type: none"> REACH 	1907/2006/EG

Unmanaged Switch PROmesh U16

Technical Drawing

