www.slipring.cn

Miniature Capsule Slip Ring LPM-12G

It is also called a rotary electrical interface, commutator, collector, swivel or an electrical rotary joint. It can improve electromechanical capability, simplify system design, eliminate possible damage while rotation. It's the key apparatus of various precision rotary worktable. electric test instrument, manufacture and process control instrument.

The LPM-12G miniature slip ring is a standard, off-the-shelf unit that uses gold contacts at the rotary interface. Color-coded lead wires are used on both the stator and rotor for simplifying electrical connections. The LPM-12G allows tremendous flexibility in dealing with system size restrictions. It is available in 1-12 circuit configurations.





TEMPE -20° C to 60° C

Applications

- **V** Electrical test equipment
- Manufacturing and process control equipment
- Indexing tables
- CCTV pan / tilt camera mounts
- **Robotics**, rotary sensors, urgent illumination equipmen
- **Exhibit** / display equipment/Closed-circuit control
- Aviation , military , instrument, medical equipment.
- Min-type wire-rolling machine / Wind turbine generator

Specifications

Operating Speed	0-300 rpm
Number of Circuits	12
Voltage	240 VAC/DC
Current Rating	2 amps per circuit
Temperature Range	-20℃ to +60℃
Contact Material	Gold to Gold
Lead Size	30# silver plated copper
Lead Length	Standard 250 mm (9.843inch)
Dielectric Strength	≥500 VAC @50Hz, between each circuit
Insulation Resistance	100 MΩ @ 500 VDC
Electrical Noise	1mΩ Min

	Capsule Length	
# of Circuits	L (mm)	Part No
12	25.50	LPM-12G



The operating life of the unit depends upon temperature, rotation speed and environment.

- ✓ 12 circuits models
- **2** amps per circuit ,240VAC/DC
- Precision assembly to provide exceptional rotational life
- Speed up to 300 rpm continuous
- Gold-Gold contacts
- Flexible, color-coded, silver-plated, lead wires
- Superior handling of low level control signals
- Metal housing optional



MAXIMUM OPERATING SPEED 0-300 RPM





Drawings

HNPAT

Advantage




- **V** Low torque minimize system torque budget
- **Compact design to fit in the most demanding space.**
- Smooth running
- ✓ Low electrical noise
- **V** Quick shipment per your urgent requirement
- **360** continuous rotation
- **W** High bandwidth transfer capability
- Addition of special components
- **Quick shipment**

		W	/re Coloi	r Code				
Wire Size	Ring #	Color	Ring #	Color	Ring #	Color	Ring #	Color
AWG17# silver plated copper Teflon UL	#1	BLK	#2	BRN	#3	RED	#4	ORG
	#5	YEL	#6	GRN	#7	BLK-BLU	#8	PUR
	#9	GRAY	#10	WIT	#11	PINK	#12	AZURY
	#13	WIT/BLK	#14	WIT/BRN	#15	WIT/RED	#16	WIT/ORG
	#17	WIT/YET	#18	WIT/GRN	#19	WIT/BLU	#20	WIT/PUR
	#21	WIT/GRAY	#22	CLAR	#23	BLK-RED	#24	BLK/BRN

Remarks: 1. AWG28# silver plated copper Teflon UL, 24 different color single wires for a circle

2. #1 from rotor side (The color if the wire can be changed).

Contact us on wire color codes



and a second on the second

Any questions about slip ring,pleas	se i	e
-------------------------------------	------	---

Circuits Signal details Dimension Operating Environment Other





Model: LPM-12G

Rotor Side | Stator Side

eave your message to get a professional solution

- Current&voltage
- Working speed
- Working temperature

Surveillance Crane Medical Marine Defence Radar antenna **Automation** Meter and instrument Wind turbine generator **VR** Device Other

